WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 5: (11) International Publication Number: **WO 93/12770** A1 A61K 9/20 (43) International Publication Date: 8 July 1993 (08.07.93)

(21) International Application Number: PCT/US92/09273

4 November 1992 (04.11.92) (22) International Filing Date:

(30) Priority data: 20 December 1991 (20.12.91) US 811,411

(60) Parent Application or Grant (63) Related by Continuation 811,411 (CIP) 20 December 1991 (20.12.91) US Filed on

(71) Applicant (for all designated States except US): PFIZER INC. [US/US]; 235 East 42nd Street, New York, NY 10017 (US).

(72) Inventors; and

US]; 48A Nob Hill Road, New London, CT 06320 (US).

(74) Agents: RICHARDSON, Peter, C. et al.; Pfizer Inc., 235 East 42nd Street, New York, NY 10017 (US).


(81) Designated States: CA, FI, JP, US, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, SE).

Published With international search report.

(54) Title: POROUS SHAPED DELIVERY DEVICES AND METHOD OF PRODUCING THEREOF

(57) Abstract

High strength, high porosity delivery devices have a shaped surface and disintegrate quickly in an aqueous medium. The devices can be prepared by disposing a formulation in a die to form a frozen predevice. A second die is contacted with the frozen formulation surface at a pressure and temperature for a time sufficient to locally momentarily liquify and shape the device surface. The shaping is followed by lyophilization.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	FR	France	MR	Mauritania	
AU	Australia	GA	Gabon	MW	Malawi	
BB	Barbados	GB	United Kingdom	NL	Netherlands	
BE	Belgium	GN	Guioca	NO	Norway	
BF	Burkina Faso	GR	Greece	NZ	New Zealand	
		HU	liungary	PL.	Poland	
BC	Bulgaria	1E	Ircland	PT	Portugal	
BJ	Benin	π	Italy	RO	Romania	
BR	Brazil	JP	Japan	RU	Russian Federation	
CA	Canada	KP	Democratic People's Republic	SD	Sudan	
CF	Central African Republic	Br	of Korea	SE	Sweden	
CC	Congo	***	Republic of Korea	SK	Slovak Republic	
CH	Switzerland	KR		SN	Senegal	
CI	Côte d'Ivoire	KZ	Kazakhstan	SU	Soviet Union	
CM1	Cameroon	u	Liechtenstein	TD	(had	•
cs	Czechuslovakia -	LK	Sri Lanka	TC		
CZ	Czech Republic	LU	Luxembourg		Togo	
DE	Germany	MC	Munaco	UA	Ukraine	•
DK	Denmark	MC	Madagascar	US	United States of America	
ES	Spain	Ml.	Mali	VN	Vict Nam	
FI	Finland	MN	Mongolia			

20

30

POROUS SHAPED DELIVERY DEVICES AND METHOD OF PRODUCING THEREOF BACKGROUND OF THE INVENTION

This invention relates to delivery devices, particularly pharmaceutical tablets, and methods for making thereof.

Pharmaceutical tablets are often administered orally. A rapid disintegration of the tablet in the mouth without mastication or water facilitates administration to patients in general, and to the very young, the elderly, and to non-human animals, in particular.

One type of oral dosage form which is designed to address the problem of swallowing is known as "chewable tablets". These tablets, however, are not fully satisfactory because they require mastication.

Another type of oral dosage form known as the "effervescent tablet" comprises solid adjuvants of an acid and a base. The reaction between the acid and the base in the presence of water gives off carbon dioxide which "blows apart" the tablet to facilitate its dissolution. One type of effervescent tablet that must dissolve in a glass of water for administration requires that the patient drink the water. Aside from the problem of leaving a small amount of residual active agent in the glass, this dosing method is impractical for very young patients. Another type of effervescent tablet that "bubbles" and then dissolves in the mouth is also objectionable to some patient populations, especially the very young. Both types of effervescent tablets are thus not fully satisfactory.

Yet another type of oral dosage form known as the "enteric tablet" is designed to release the pharmaceutical agent in the upper small intestine. A limitation of enteric tablets is that those that fail to disintegrate rapidly in the intestine could pass the "window of absorption" and result in poor bloavailability.

One type of non-oral dosage form known as the birth control pessaries often takes as long as ten minutes to release the foaming agent. For obvious reasons, it is desirable for this type of dosage form to disintegrate rapidly.

Tablets that disintegrate rapidly in an aqueous environment are often formulated with disintegration agents, such as starch, microcrystalline cellulose, carboxymethylcellulose sodium, and sodium starch glycolate, etc. These tablets disintegrate at an unsatisfactory rate for some applications described above.

25

An increased disintegration rate can be obtained by increasing the porosity (void spaces) of the tablet. Void spaces in the tablet matrix facilitate the permeation of water to rapidly erode the entire tablet. It is easily understood that a higher porosity of the tablet implies a faster disintegration in an aqueous 5 environment. It is therefore desirable to obtain tablets of the highest porosity technically achievable.

U.S. Patent No. 3,885,026 discloses a process for the production of porous tablets. In this process, a solid volatilizable adjuvant is incorporated in the tablet formulation. The tablet is formed by compression, and the volatilizable adjuvant is 10 removed by sublimation or thermal decomposition. Exemplary volatilizable adjuvant include urethane, urea, ammonium bicarbonate, hexamethylenetetramine, benzoic acid, phthalic anhydride, naphthalene and camphor. The maximum porosity obtained according to this patent is 50% and preferably 10 to 30%. Strong tablets of a porosity higher than 50% are difficult to produce by this method.

U.S. Patent No. 4.134,943 discloses the production of porous tablets by mixing the tablet components with a liquid solvent which is inert towards the tablet components. Suitable solvents include water, cyclohexane, benzene, etc., which freeze at a temperature from about -30 to +25°C. The solvent constitutes about 5 20 to 80% by weight of the total mixture. The mixture is divided or sprayed into small particles or droplets which are subsequently frozen into solid flowable granules. These granules are pressed into tablets at a temperature below the freezing point of the solvent, and then the solvent is sublimed from the tablets. The porosity of the resultant tablets corresponds to the amount of solvent that is removed from the tablet. The maximum porosity of the tablets produced by this method is 80%. The method of production in this patent is relatively complex since it involves the preparation of frozen granules.

Finally, U.S. Patent Nos. 4,305,502 and 4,371,516 disclose the production of shaped articles by freezing, in a mold, a water-based pharmaceutical 30 composition, and subliming the water from the frozen composition to form porous articles. These processes do not include compression of the articles and therefore lack the ability to produce a specifically desired shape of the article on the side of

the mold that is open. Because the articles produced by this process have a weak, easily broken meniscuses, U.S. Patent No. 4,305,502 reduces the amount of handling of the articles by forming them *in situ* in the depressions of a filmic packaging substrate. The method in both patents allows only one side of the article to be imprinted. It is therefore difficult to include both the company logo and the drug identification on one dose unit as usually desired.

Although there are a variety of methods for making porous tablets, these methods do not adequately address all the problems. For example, processes are complex, tablets lack sufficient porosity, tablets are not shaped, tablets are weak and fragile. Accordingly, there is a continual search in this art for highly porous, strong, shaped tablets.

SUMMARY OF THE INVENTION

This invention is directed to high strength, high porosity delivery devices that have a molded shape over substantially their entire surface area and disintegrate rapidly in an aqueous medium. The tablets comprise about 5% to about 95% water soluble polymer and an active agent.

Another aspect of this invention is directed to a simple method of making strong, highly porous, shaped delivery devices. The method comprises disposing a formulation in a first die and freezing the formulation to form a frozen predevice. A second die is contacted with the frozen predevice surface at a pressure and temperature for a time sufficient to locally liquify, shape, and refreeze the predevice surface. The shaped frozen predevice is lyophilized to form the highly porous device. Preferably, the formulation includes at least one water soluble polymer and at least one beneficial agent.

25 This invention makes a significant advance in the field of delivery devices by providing high strength, highly porous devices that have a molded shape over their entire surface area and disintegrate rapidly in an aqueous medium. This invention also provides a simple efficient method for the production of such devices.

Other features and advantages will be apparent from the specification and claims, and from the accompanying drawings illustrating an embodiment of the invention.

20

25

30

BRIEF DESCRIPTION OF DRAWINGS

Figure 1 is a schematic (in cross-section) illustrating the filling of a die with the liquid formulation.

Figure 2 is a schematic (in cross-section) illustrating the formulation-filled die being frozen.

Figure 3 is a schematic (in cross-section) illustrating contact of the top punch with the die and frozen formulation meniscus.

Figure 4 is a schematic (in cross-section) illustrating the shaping of the frozen formulation by the top punch.

Figure 5 is a schematic (in cross-section) illustrating the release of the top punch from the die.

Figure 6 is a schematic (in cross-section) illustrating the ejection of the shaped frozen formulation (predevice) from the die by the bottom punch.

Figure 7 is a schematic perspective view of the top punch, bottom punch and shaped predevice.

DETAILED DESCRIPTION OF THE INVENTION

Any water soluble polymer may be employed as the strengthening substance in the devices of this invention. Water soluble polymer is also meant to include lightly cross-linked fine particle polymers, for example, carbomer which is an acrylic acid polymer cross-linked with a polyalkenyl polyether. Preferably, the water soluble polymer is a film-forming polymer. By "film-forming polymers" is meant, as described in "The Theory and Practice of Industrial Pharmacy" by Lachman, Lieberman and Kanig (1970), polymers which are sufficiently soluble in the solvent and are capable of producing a strong continuous film. These water soluble polymers act as a binder to provide sufficient adhesion to enable the device to maintain its structural shape. Preferably, the water soluble polymer is gurn arabic, agar, alginic acid, carbomer, carboxymethylcellulose calcium, carboxymethylcellulose sodium, carrageenan, chitosan, dextrin, gelatin, guar gurn, hyaluronic acid, hydroxyethyl cellulose, hydroxypropyl cellulose, hydroxypropyl methylcellulose, methyl-cellulose, pectin, poloxamer, polyethylene glycol,

WO 93/12770 PCT/US92/09273

-5-

polyacrylamide, polyvinyl alcohol, poly(N-vinylpyrrolidone), propylene glycol alginate, sodium alginate, tragacanth or xanthum gum. It is especially preferred that gelatin, pectin, hydroxypropyl cellulose, poly(N-vinylpyrrolidone) or carbomer be used.

5

20

25

30

Generally, the water soluble polymer comprises about 1% to about 10% of the predevice formulation composition. These quantities provide the finished device with sufficient strength and a satisfactory dissolution rate. It is preferred that about 2% to about 4% of the predevice formulation be water soluble polymer, and especially preferred that about 2% to about 3% of the predevice formulation be water soluble polymer. These above percentages correspond to about 5% to about 95% (preferably about 5% to about 30%) of the weight of the actual device (i.e. after lyophilization).

The devices of this invention comprise, in addition to the water soluble polymer, one or more beneficial agents. The term "beneficial agents" as used in this specification and the accompanying claims includes, by way of example and not of limitation, any physiologically or pharmacologically active substance that produces a localized or systemic effect in animals. The term "animals" is meant to include mammals including human beings as well as other animals. The physiologically or pharmacologically active substance of this invention need not be soluble in water.

Examples of active substances employed in the devices of this invention include, without limitation, inorganic and organic compounds, such as drugs that act on the peripheral nerves, adrenergic receptors, cholinergic receptors, nervous system, skeletal muscles, cardia-vascular smooth muscles, blood circulatory system, synaptic sites, neuroeffector junctional sites, endocrine and hormone systems, immunological system, reproductive system, autacoid systems, alimentary and excretory systems, and inhibitors of autocoids and histamine systems. Drugs that can be delivered for acting on these systems include anti-depressants, hypnotic, sedatives, psychic energizers, tranquilizers, anti-convulsants, muscle relaxants, antisecretories, anti-parkinson agents, analgesics, anti-inflammatory agents, local anesthetics, muscle contractants, antibiotics, anti-microbials, anthelmintics, anti-malarials, hormonal agents, contraceptives,

histamines, antihistamines, adrenergic agents, diuretics, antiscabiosis, antipediculars, anti-parasitics, anti-neoplastic agents, hypoglycemics, electrolytes, vitamins, diagnostic agents and cardiovascular drugs. Especially preferred pharmaceutical agents include ascorbic acid, acetamino-phen, acetylsalicylic acid, diphenhydramine, doxylamine succinate, meclizine, pseudoephedrine HCl, azithromycin, erythromycin, sultamicillin tosylate, amoxicillin trihydrate, sulbactam sodium, nifedipine, doxazosin mesylate, amlodipine besylate, glipizide, perbuterol HCl, fluconazole, piroxicam, tenidap, sertraline HCl, cetirizine and denofloxacin. Preferably, the formulation includes a unit dose of the beneficial agents. The amount of the beneficial agent employed is based on the clinically established efficacious dose, which ranges from about 0.01 mg to about 1000 mg. The weight ratio of said active ingredient to the carrier is in the range of 1:1 to 1:2500.

Also included in such beneficial agents are prodrugs of the above-described drugs. Such drugs or prodrugs can be in a variety of forms such as the pharmaceutically acceptable salts thereof, and they need not be water soluble. It is within the scope of this invention that the devices can contain more than one beneficial agent.

The beneficial agents of this invention also include substances for which it is desirable and/or advantageous to control delivery into an environment of use. Examples of such agents, include, but are not limited to, fertilizers, algacides, reaction catalysts, enzymes, and food or drink additives.

In addition to the above described components, other common pharmaceutical excipient may be used. These excipient are generally known in the art, for example, as described in Remington's Pharmaceutical Sciences, 18th Edition (1990), particularly pages 1633 to 1638, and in the Handbook of Pharmaceutical Excipient by the American Pharmaceutical Association. Exemplary excipient include flavoring agents such as natural and artificial orange flavor, grape flavor, artificial banana flavor, strawberry flavor, cherry flavor, peppermint, fruit punch flavor and bubble gum flavor, sweetening agents such as sucrose, aspartame, and alitame, coloring agents such as FD&C red #3 and #40, FD&C yellow #5 and #6, and FD&C blue #2, lubricating agents such as magnesium stearate, sodium lauryl sulfate, talc, polyethyleneglycols, stearic acid, hydrogenated

20

vegetable oils, corn starch, sodium benzoate and sodium acetate, disintegrants such as corn starch, complex silicates, sodium carboxymethyl starch, microcrystalline cellulose, sodium alginate, alginic acid, cross-linked polyvinylpyrrolidone and carboxymethylcellulose sodium, diluents such as lactose, sucrose, dextrose, mannitol, xylitol, sorbitol, sodium chloride, and dibasic calcium phosphate, suspending agents such as acacia, bentonite, calcium stearate, carbomer, gelatin, guar gum, hydroxypropyl cellulose, methyl cellulose, polyvinyl alcohol, povidone, sodium alginate, tragacanth and xanthan gum, emulsifying agents such sodium lauryl sulfate, polyoxyethylene sorbitan monooleate, sorbitan monolaurate, poloxamers, lecithin, acacia, emulsifying wax, and polyethylene stearate. As is clear from the above, the same exciplent may be used for different purposes within the same devices of this invention. For example, mannitol and xylitol can be used as both the diluents and the strengthening substances in the device.

The remainder of the formulation is water. The amount of water is selected to achieve the desired porosity subsequent to lyophilization.

The porous devices of this invention have sufficient porosity to provide the devices with the desired strength and dissolution rate. Preferably, the porosity is from about 85% to about 98%. The term "porosity" of a tablet as used herein refers to the void spaces created by the removal of water from the tablet by lyophilization. Since the dimensions of the lyophilized tablet are unchanged. "porosity" can be expressed either as the percentage of void spaces by volume in the lyophilized tablet, or as the percentage of water by weight in the tablet formulation prior to lyophilization. Preferably, the porosity is about 90% to about 95%. The devices have an open matrix network. This structure is expressed as a network of water-soluble carrier material having interstices dispersed throughout. The open matrix network of the carrier material is of generally low density. For example the density may be within the range of 10 to 400 mg/cc, preferably 30 to 150 mg/cc, more preferably 60 to 150 mg/cc. The density of the shaped device may be affected by the amount of pharmaceutical substance, or other chemical, or any other ingredients incorporated into the device, and may be outside the abovementioned limits for the density of the matrix network. The open matrix network. which is similar in structure to a solid foam, enables a liquid to enter the product

15

25

through the interstices and permeate through the interior. Permeation by aqueous media exposes the carrier material of both the interior and exterior of the device to the action of the aqueous media resulting in rapid disintegration of the matrix network. The open matrix structure is of a porous and capillary nature which enhances disintegration of the product as compared with ordinary solid shaped pharmaceutical dosage forms, such as tablets, pills, capsules, suppositories and pessaries. Rapid disintegration results in rapid release of any pharmaceutical substance or other chemical carried by the matrix.

The porous tablets have high strength (i.e., low friability) as a result of their laminate structure. By "laminate structure" is meant that thin walls of the water soluble polymer are compacted. Between the walls are the open spaces where the water was prior to lyophilization. This laminate structure strengthens the tablet, and the open spaces (expressed as capillaries) greatly facilitate the permeation of water and the dissolution of the device.

In addition, the devices are shaped (i.e., have a predetermined molded shape) over substantially their entire surface area. By "shaped" is meant that the surface has a form that would not naturally occur through the mere action of gravity or surface tension (such as a meniscus). This molded shape may take any form, such as concave round, dual-radius, octagon, oval, or saddle, optionally with bevelled edges or shaped patterns, and preferably includes molded symbols on the surface. The symbols may include logos, brand names, drug identification, doses, etc. Advantageously, these symbols may be present on more than one "side" of the device since the devices are molded over substantially all their surface area.

The devices of this invention may be made by any process that results in the tablets having the desired combination of strength, porosity, disintegration rate and shape.

In the method of producing the shaped devices of this invention, any substantially water-soluble solid can be employed as the "strengthening substance" (i.e., the carrier) in the device. Exemplary water-soluble solids, in addition to the above polymers include, but are not limited to, vitamins such as ascorbic acid; amino acids such as glycine, arginine and phenylalanine; monosaccharides such as glucose and fructose; disaccharides such as maltose and lactose; polyhydroxy

25

30

alcohols such as mannitol and xylitol, carboxylic acids such as phenylacetic acid, L-glutamic acid, adipic acid, L-tartaric acid, citric acid and succinic acid; derivatives of carboxylic acids such as urea (an amide); salts of carboxylic acids such as tartrazine (FD&C yellow #5) and sodium citrate; amines such as glutamine; alcohols such as cinnamyl alcohol; and inorganic salts such as potassium chloride, sodium chloride and monosodium glutamate.

Generally, the devices of this invention are made by freezing the desired formulation in a die and contacting another die with the exposed device surface at a pressure and temperature for a time sufficient to locally liquify, and shape the surface and then immediately re-freeze the shaped surface in <u>situ</u>.

The frozen device is then lyophilized. By "locally liquify" is meant sufficient portions of the formulation remain solid so that there is substantially no formulation leakage from the die. Preferably, the ingredients are combined to form a slurry, solution, or suspension using standard formulation techniques, and the resulting formulation is disposed in a die having the desired shape. The dies used in this process may advantageously have particular insignias in order to impart a logo, brand name, dose, drug identification, etc., to the finished devices. The formulation is then exposed to an environment sufficient to lower the temperature of the formulation below its particular eutectic point. Typically, for the formulations described herein, the temperature is below about 0°C. Preferably the temperature is below about -30°C.

Once frozen, a second shaped die is disposed in contact with as much of the remaining surface (i.e., the exposed surface) as is desired. Typically, substantially all of the exposed surface is formed by locally liquifying, shaping, and re-freezing the surface. The phenomenon of liquefying under pressure is due to an unusual behavior of water; i.e., the melting point of ice is decreased by increasing pressure. The localized liquification differentiates this process from processes where shaping is performed by a compression of granulated substances; upon compression of granulated substances, particles are fractured and forced close to one another and bonded by ionic or van der Waals interaction. Generally, in the present invention, the die is contacted with the exposed predevice surface at a pressure of about 0.5 kg/cm² to 9,000 kg/cm² at a temperature of from about 200°C to about -78°C over a period of about 1 second to about 1 minute.

Preferably, the die contacts the exposed device surface at a pressure of about 450 kg/cm² to about 2500 kg/cm² and at a temperature of about -30°C to about 60°C for about 1 second to about 10 seconds. Clearly, there is a time-temperature-pressure dependency, and those skilled in the art can readily select the appropriate combination to achieve the desired effect (i.e., production of the devices described herein). Preferably, a mold release system is employed. This system may comprise a die formed of a conventional release type material such as polytetrafluoroethylene or anodized aluminum, or the die may be coated with conventional release films such as ethanol, calcium stearate, magnesium stearate, silicone grease or polytetrafluoroethylene.

Once molded, the frozen device is typically released from the mold and lyophilized (freeze dried) (although it need not be released for lyophilization to occur) so that the solvent (i.e., water) sublimes, resulting in the porous device described herein. The lyophilization may be performed by subjecting the molded device to reduced pressure and, if desired, to controlled application of heat to aid the sublimation. The pressure can be below about 4 mm Hg and is preferably below 0.3 mm Hg, for example 0.1 to 0.2 mm. The temperature may be about -40°C to about 20°C.

Referring to the drawings, there is illustrated in Figure 1 a cylindrical die 1, through which a bottom punch 3 is mated by sliding. A filling apparatus 4 deposits the liquid formulation 6 in the cavity formed by the die 1 and punch 3. A refrigeration unit 12 is disposed in contact with the die 1. According to figure 2, the desired amount of liquid formulation 6 has been disposed in the cavity formed by the die 1 and punch 3, and is exposed to freezing temperatures by the refrigeration unit 12. According to Figure 3, the frozen formulation 7 is disposed between the bottom punch 3, die 1 and top punch 15. According to Figure 4, the shaped frozen formulation 8 has been compressed between the bottom punch 3, die 1 and top punch 15 is removed, and then the frozen shaped formulation (predevice) 8 is ejected from the die 1 by the action of the bottom punch 3, as depicted in Figure 6. The shaped predevice may then be conveniently lyophilized. Figure 7 depicts the shaped imprints on the top 24 and bottom 27 of the frozen predevice 8 which were made by the corresponding molded shapes 18, 21 of the top punch 15 and bottom punch 3.

25

30

The freeze-dried devices are then available for use as desired. These devices may be used for the oral delivery of pharmaceutical agents to animals, including mammals, particularly man. These oral delivery devices can be administered as is or dissolved in water prior to administration. In addition, the devices may be utilized for alternative delivery as suppositories, ocular inserts, inplants, etc. Finally, these delivery devices may be used to deliver a variety of active ingredients to diverse environments. Exemplary ingredients include fertilizers for agricultural environments, food flavorings for cooking and baking, and sweeteners and cream for coffee and other drinks.

The devices and processes of this invention make a significant advance in the field of delivery devices. The devices are highly porous, which facilitates rapid dissolution or disintegration. The rapid dissolution or disintegration facilitates swallowing without water or mastication or both. The rapid dissolution rate facilitates the use of the device in those instances where such devices are desirable (e.g., veterinary delivery, pediatric patients, geriatric patients). The high strength maintains the device as an integral unit during conventional packaging, transporting and handling, thus assuring the physical integrity of the dosage form, and assuring that the patient receives the proper dosage. The molded shape aids in maintaining the device as an integral unit in comparison to compressionless tablets that can have weak, easily broken meniscuses. Finally, the molded shape also provides for identification on all surfaces with symbols, e.g., logos. In addition to the marketing advantages, this identification can also be used to aid in assuring a tablet's authenticity.

In the following Examples (below), the delivery devices' strength and disintegration rates were determined by a friability test and a disintegration test.

Friability is a measure of tablet strength. The measurement is based on tablet weight loss, expressed as a percentage, after certain numbers of revolutions in the Vanderkamp Friabilator. A low friability value represents better tablet strength.

Disintegration time is measured by the Stoll-Gershberg method using the Erweka tester. The tablet is placed in a perforated basket which is immersed in a 37°C water bath. During the test, the basket moves in an up-and-down motion.

The time needed for complete disintegration of the tablet is recorded as the disintegration time.

The materials used in the follow	ing Examples are as follows:
----------------------------------	------------------------------

Water:

distilled

5

Gelatin:

150 bloom; General Foods

Corporation

Pectin:

low methoxyl pectin; Sunkist

Growers

10

Carbopol 934P:

carbomer; The B. F. Goodrich

Company

Klucel EF:

hydroxypropylcellulose; Aqualon

Company

Povidon C30:

poly(N-vinylpyrrolidone); GAF

Corporation

Calcium chloride:

calcium chloride dihydrate;

Fisher Scientific

Mannitol:

Ruger Chemical Company

Xylitol:

American Xyrofin Inc.

20

15

Aspartame:

Nutrasweet; Nutrasweet Company

Orange flavor:

natural and artificial orange

flavor; Firmenich Inc.

25

30

35

Grape flavor:

spray dried natural and artificial grape flavor;

Food Materials Corporation

Fluconazole:

anti-fungal agent; Pfizer Inc

Microencapsulated

fluconazole:

fluconazole coated with

Surelease/Opadry.; 70% drug

potency; Pfizer Inc

Piroxicam:

anti-inflammatory agent; Pfizer Inc

Pheudoephedrine

HCI:

decongestant; Knoll Fine

Chemical.

EXAMPLE 1

Gelatin was dissolved in warm water (55°C) followed by the addition of mannitol, aspartame, and the encapsulated orange flavor. Each 1,000 mg solution contained the following:

<u>5</u>	Tablet A Ingredients	Mg/tablet	
	Water	(930) later removed	
	Gelatin	25	
•	Mannitol	35	
	Aspartame	5	
<u>10</u>	Orange flavor	5	
	TOTAL	(1000) 70	

A die-and-punch assembly was lubricated with silicone grease and pre-cooled in a dry-ice container (-78°C). The above solution was charged into the tableting die with the bottom punch in place. After the solution in the die was frozen and cooled to about 26°C, a pre-cooled top punch was placed into the die. Using a Carver press, a force of 5,000 pounds was applied to the punch to momentarily liquify the top surface of the frozen mass. After the pressure was released, the top punch was removed. The frozen, shaped tablet was then pushed out of the die. The water in the tablet was removed by lyophilization. The final tablet had the 20 shape and the imprint in three dimensions from the tableting die and punches (0.375 inch by 0.875 inch oval, 0.250 inch thick). The porosity of the tablet was 93% based on the amount of water removed by lyophilization.

Friability after 100 revolutions:

0.0%.

Disintegration time: 4 seconds.

<u>25</u>

EXAMPLE 2

The same formulation as in Example 1 was charged into a pre-cooled dieand-punch assembly. The top punch was kept at 60°C before being brought into contact with the frozen mass in the die. Using a Carver press, the punches were applied with a force of 1,000 pounds which was sufficient for the warm punch to momentarily liquify the surface of the frozen mass. The top punch was then removed and the tablet was pushed out of the die. The tablet was lyophilized as in Example 1 to yield a 93% porous tablet (Tablet B) which had the shape and the imprint in three dimensions from the tableting die and punches (0.375 inch by 0.875 inch oval, 0.250 inch thick).

Friability after 1000 revolutions:

0.0%.

<u>5</u>

<u>10</u>

<u>15</u>

<u>20</u>

Disintegration time:

4 seconds.

EXAMPLE 3

Solution A: Low-methoxyl pectin (5 g) was blended with warm water (150 g) in a blender for one minute and let stand for 5 minutes.

Solution B: Mannitol (25 g), calcium chloride dihydrate (0.25 g), and the encapsulated orange flavor (2 g) were added to water (275 g). The pH of this solution was adjusted to 3.2 with citric acid. The solution was heated to 80°C.

Solution A and solution B were mixed with stirring and allowed to cool. Following the procedure in Example 1, frozen tablets were made using the precooled die and punches. Each 1,000 mg tablet contained the following:

Tablet C Ingredients	Mg/tablet
Water	(929) later removed
Pectin	11
Mannitol	55
Calcium chloride	0.6
Orange flavor	4.4
TOTAL	(1000) 71

Using a Carver press, each tablet was three dimensionally molded and imprinted (0.375 inch by 0.875 inch oval, 0.250 inch thick) with a force of 5,000 pounds applied to the punches. The final, lyophilized tablet was 92.9% porous.

Friability after 100 revolutions:

0.0%.

Disintegration time:

22 seconds.

Example 4

Povidone C30 was dissolved in water followed by the addition of mannitol, aspartame, and the encapsulated orange flavor. Each 1,000 mg solution contained the following:

<u>5</u>	Tablet D Ingredients	Mg/tablet	
	Water	(930) later removed	
	Povidon C30	25	
	Mannitol	35	
	Aspartame	5	
10	Orange flavor	5	
	TOTAL	(1000) 70	

Three dimensionally molded and imprinted tablets (0.375 inch by 0.875 inch oval, 0.250 inch thick) of 93% porosity were made by following the procedure in Example 1.

<u>15</u>

Friability after 30 revolutions:

1.6%

Disintegration time:

2 seconds.

Example 5

Klucel-EF (hydroxpropyl cellulose) was dissolved in water followed by the addition of mannitol, aspartame, and the encapsulated orange flavor. Each 1,000 mg solution contained the following:

Tablet E Ingredients	Mg/tablet	
Water	(930) later removed	
Klucel EF	25	
Mannitol	35	
Aspartame	5	
Orange flavor	5 ·	
TOTAL	(1000) 70	

<u>25</u>

Three dimensionally molded and imprinted tablets (0.375 inch by 0.875 inch oval, 0.250 inch thick) of 93% porosity were made by following the procedure in Example 1.

Friability after 30 revolutions:

1.4%.

<u>5</u>

Disintegration time:

12 seconds.

Example 6

Carbopol 934P was dissolved in water followed by the addition of mannitol, aspartame, and the encapsulated orange flavor. Each 1,000 mg solution contained the following:

<u>10</u>

the state of the s		
Tablet E Ingredients	Mg/tablet	
Water	(930) later removed	
Carbopol 934P	10	
Mannitol	50	
Aspartame	5	
Orange flavor	5	
TOTAL	(1000) 70	

<u>15</u>

Three dimensionally molded and imprinted tablets (0.375 inch by 0.875 inch oval, 0.250 inch thick) of 93% porosity were made by following the procedure in Example 1.

<u>20</u>

Friability after 30 revolutions:

5.6%.

Disintegration time:

4 seconds.

Example 7

Carbopol 934P was dissolved in water followed by the addition of mannitol, aspartame, the encapsulated orange flavor and Fluconazole. Each 1,052.5 mg solution contained the following:

<u>5</u>

<u>15</u>

Tablet G Ingredients	Mg/tablet	
Water	(930) later removed	
Carbopol 934P	10	
Mannitol	50	
Aspartae	7.5	
Fluconazole	50	
Orange flavor	5	
TOTAL	(1052.5) 122.5	

Example 8

Xylitol, mannitol, and the encapsulated orange flavor were dissolved in water. Each 1,000 mg solution contained the following:

Tablet H Ingredients	Mg/tablet	
Water	(650) later removed	
Xylitol	130	
Mannitol	195	
Orange flavor	25	
TOTAL	(1000) 350	

Three dimensionally molded and imprinted tablets (0.375 inch by 0.875 inch oval, 0.250 inch thick) of 65% porosity were made by following the procedure in 20 Example 1.

Friability after 30 revolutions:

3.3%.

Disintegration time:

2 seconds.

Example 9

Gelatin was dissolved in warm water followed by the addition of mannitol, aspartame, microencapsulated fluconazole, xanthan gum and the encapsulated orange flavor. Each 1,521.6 mg solution contained the following:

	Tablet I Ingredients	Mg/tablet
	Water	(1317) later removed
	Gelatin	40
	Mannitol	10
<u>5</u>	Aspartame	5
_	Microencapsulated Fluconazole	143
	Xanthan gum	1.6
	Orange flavor	5
<u>10</u>	TOTAL	(1521.6) 204.6

Three dimensionally molded and imprinted tablets (0.375 inch by 0.875 inch oval, 0.350 inch thick) of 86.5% porosity were made by following the procedure in Example 1.

Friability after 100 revolutions:

0.0%.

<u>15</u>

Disintegration time:

14 seconds.

Example 10

Gelatin was dissolved in warm water followed by the addition of mannitol, aspartame, the encapsulated grape flavor, and pheudoephedrine hydrochloride. Each 1,000 mg solution contained the following:

2	\mathbf{a}
_	v

<u>25</u>

Tablet J Ingredients	Mg/tablet	
Water	(900) later removed	
Gelatin	25	
Mannitol	40	
Aspartame	3	
Pheudoephedrine HCl	30	
Grape flavor	2	
TOTAL	(1000) 100	

Three dimensionally molded and imprinted tablets (0.375 inch by 0.875 inch oval, 0.225 inch thick) of 90% porosity were made by following the procedure in Example 1.

Friability after 100 revolutions:

0.0%.

<u>5</u>

Disintegration time:

1 second.

Example 11

Gelatin was dissolved in warm water followed by the addition of mannitol, aspartame, the encapsulated grape flavor, and piroxicam. Each 1,000 mg of piroxicam suspension contained the following:

Tablet K Ingredients	Mg/tablet
Water	(900) later removed
Gelatin	2●
Mannitol	50
Aspartame	3 .
Piroxicam	20
Grape flavor	2
TOTAL	(1000) 100

Three dimensionally molded tablets (0.625 inch deep-round-concave, 0.175 inch thick) of 90% porosity were made by following the procedure in Example 1.

<u>20</u>

<u>25</u>

Friability after 100 revolutions:

0.0%.

Disintegration time:

1 second.


It should be understood that the invention is not limited to the particular embodiments described herein, but that various changes and modifications may be made without departing from the spirit and scope of this novel concept as defined by the following claims.

CLAIMS

- 1. A porous, shaped delivery device comprising:
 - a). about 5% to about 95% water soluble polymer; and
 - b). an active agent; wherein said device has a porosity of at least about 85% and said device has a molded shape over substantially the entire device surface.
- 2. The device as recited in claim 1 wherein said water soluble polymer is gelatin, pectin, hydroxypropyl cellulose, poly(N-vinylpyrrolidone) or carbomer.
- 3. The device as recited in claim 2 wherein said beneficial agent is a pharmaceutical agent.
- 4. The device as recited in claim 3 wherein said pharmaceutical agent is fluconazole, piroxicam or pheudoephedrine HCI, azithromycin, sertraline, or cetirizine.
- 5. The device as recited in claim 4 wherein said device comprises about 5% to about 30% water soluble polymer.
 - 6. A method for making a porous shaped delivery device comprising:
 - a). disposing a formulation into a first die;
 - b). freezing said formulation to form a frozen predevice;
 - c). contacting a second die with the exposed frozen predevice surface at a pressure and temperature for a time sufficient to locally liquify, shape and refreeze said surface; and
 - d). Iyophilizing said frozen predevice to form said porous, shaped delivery device.
- 7. The method as recited in claim 6 wherein said formulation includes a water soluble polymer.
- 8. The method as recited in claim 7 wherein said formulation includes a pharmaceutical agent.
- 9. The method as recited in claim 8 wherein said formulation includes at least about 85% water.
- 10. The method as recited in claim 9 wherein said pressure and temperature ranges from 0.5 kg/cm² at 200°C to 9,000 kg/cm² at -78°C over a period of 1 second to 1 minute.


- 11. The method as recited in claim 9 wherein said water soluble polymer is gelatin, pectin, hydroxypropyl cellulose, poly(N-vinylpyrrolidone), or carbomer.
- 12. The method as recited in claim 11 wherein said pharmaceutical agent is fluconazole, piroxicam, pheudoephedrine HCl, azithromycin, sertraline, or cetirizine.
- 13. The method as recited in claim 12 wherein said pressure and temperature ranges from 2,500 kg/cm² at -30°C to 450 kg/cm² at 60°C over 1 second to 10 seconds.
- 14. The method as recited in claim 13 wherein said pharmaceutical agent is fluconazole and said water soluble polymers are gelatin and carbomer.
- 15. The method as recited in claim 14 wherein said device contacts a mold release material integral to or applied to said die.

PCT/US92/09273



2/2

FIG. 7



International Application No

L CLASS	IFICATION OF SUBJ	ECT MATTER (if several dessifie	ration curried cools indicate all 6	
		t Classification (IPC) or to both Nat		
	1. 5 A61K9/20		Caracana and as C	
IL FIELD	S SEARCHED			
		Minimum I	Documentation Searched?	
Chssific	ation System		Classification Symbols	
	_			
Int.Cl	. 5	A61K		
-	-	Documentation Searched	other than Minimum Documentation	
		to the Extent that such Docum	sents are included in the Fields Searched	
		D TO BE RELEVANT		
Category °	Citation of Do	cument, 11 with indication, where app	propriate, of the relevant passages 12	Relevant to Claim No.13
X	ED 4 2 2	66 025 / 10UN LAPETIE	• DOCTIED 170	
^	5 May 19	66 835 (JOHN WYETH 6	a BRUTHER LID)	1-3,5
		the application		
	& US-A-4			
	see page	4, line 14 - page (5, line 29	Ì
ļ	see page see clai	10; example 1		ĺ
	See Clai	no 7_0		
(]		09 591 (MEDIVENTURES	S INC.)	1-5
-	11 July :			
ľ		the application		
- 1		7, line 2 - line 22 23; example 8	•	
]		34; example 19		
j	see page	37; example 22		
1	see clain	ns 22,24,25,27,28		
ľ				
			-/	
			Í	
	····			
-	extegories of cited docum	eents : ¹⁰ il state of the art which is not	"T" later document published after the internati or priority date and not in conflict with the	onal filing date
consi	idered to be of particular	relevance	cited to understand the principle or theory invention	unserlying the
"E" earlie filing	er document but publishe g date	ed on or after the international	"X" document of particular relevance; the claim cannot be considered novel or cannot be con-	ed invention
"L" docum	ment which may throw do h is cited to establish the	pabts on priority claim(s) or publication date of another	myore an inventive step	
citatio	on or other special reaso	n (as specified) disclosure, use, exhibition or	"Y" document of particular relevance; the claims cannot be considered to involve an inventive	often subsection about
other	means		document is combined with one or more oth ments; such combination being obvious to a	er such docu- person skilled
	ment published prior to the character of the priority date of the priority date of the character of the published prior to the published published prior to the published publis	he international filing date but limed	in the art. "A" document member of the same patent family	
. CERTIFIC	CATION		,	
	tinal Completion of the I	nternational Search	Date of Malling of this International Search	Percet
	04 FEBRUARY			sepan .
			1 9. 02. 93,	ľ
ernational S	earching Authority		Signature of Authorized Officer	
	EUROPEAN	PATENT OFFICE	BOULOIS D.	·
		· · · · · · · · · · · · · · · · · · ·		

Form PCT/ISA/210 (mount sheet) (Jamery 198

International Application No

	International Application No	
IIL DOCUM	ENTS CONSIDERED TO BE RELEVANT (CONTINUED FROM THE SECOND SHEET)	
Category °	Citation of Document, with indication, where appropriate, of the relevant passages	Relevant to Claim No
A	FR,A,2 335 205 (BOEHRINGER MANNHEIM GMBH) 15 July 1977 cited in the application & US-A-4134943 see page 2, line 11 - line 25 see page 3, line 7 - page 4, line 28 see page 6; example 4	1-15
١	EP,A,O 081 912 (JOHN WYETH & BROTHER LTD) 22 June 1983 see page 9 - page 10; example 1	1-15
A	EP,A,O 084 705 (JOHN WYETH & BROTHER) 3 August 1983 see page 13 - page 14; example 1	1-15
		}
	·	
	•	
ľ		

ANNEX TO THE INTERNATIONAL SEARCH REPORT ON INTERNATIONAL PATENT APPLICATION NO.

US 9209273 SA 66573

This armex lists the patent family members relating to the patent documents cited in the above-mentioned international search report. The members are as contained in the European Patent Office EDP file on

The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information. 04/02/93

Patent document cited in search report	Publication date		nt family mber(s)	Publicati date
FR-A-2366835	05-05-78	GB-A-	1548022	04-07-79
		AU-B-	513845	08-01-81
		AU-A-	2882577	22-03-79
		CA-A-	1097233	10-03-81
		CH-A-	633717	31-12-82
		DE-A,C	2744493	13-04-78
		JP-C-	1446344	30-06-88
		JP-A-	53044619	21-04-78
			62050445	24-10-87
		JP-B-	78259	09-06-78
		LU-A-		
		NL-A-	7710876	10-04-78
		US-A-	4305502	15-12-81
		BE-A-	859291	30-03-78
		CA-A-	1083042	05-08-80
		JP-C-	1509556	26-07-89
		JP-A-	61118314	05-06-86
		JP-B-	63052008	17-10-88
		US-A-	4371516	01-02-83
WO-A-9109591	11-07-91	AU-A-	7171191	24-07-91
MO V 2102021		EP-A-	0460185	11-12-91
		JP-T-	4503959	16-07-92
		US-A-	5120549	09-06-92
 FR-A-2335205	15-07-77	DE-A-	2556561	30-06-77
FR A 2555205	13 07 77	AT-B-	348133	25-01-79
		BE-A-	849438	15-06-77
		CH-A-	609563	15-03-79
		GB-A-	1502580	01-03-78
		JP-C-	1192403	29-02-84
		JP-A-	56120617	22-09-81
			•	20-05-83
		JP-B-	58024410	
		JP-A-	52076420	27-06-77
		NL-A-	7613818	20-06-77
		SE-B-	423967	21-06-82
		SE-A-	7613971	17-06-77
		US-A-	4134943	16-01-79
EP-A-0081912	22-06-83	AU-B-	554816	04-09-86
	•	AU-A-	9061882	09-06-83
			,	
e details about this annex : see		 		

ANNEX TO THE INTERNATIONAL SEARCH REPORT ON INTERNATIONAL PATENT APPLICATION NO.

9209273 66573 SA

This amex lists the patent family members relating to the patent documents cited in the above-mentioned international search report.

The members are as contained in the European Patent Office EDP file on

The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

04/0

04/02/93

Ŀ

EP-A-0081912 CA-A- 1200960 25-0 GB-A,B 2119246 16-1 JP-B- 1049242 24-1 JP-C- 1568399 10-0 JP-A- 58113123 05-0 SU-A- 1514239 07-1 US-A- 4758598 19-0 EP-A-0084705 03-08-83 AU-B- 554431 21-0 AU-A- 9086982 16-0 CA-A- 1195250 15-1	EP-A-0081912 CA-A- 1200960 25-02-8 GB-A,B 2119246 16-11-8 JP-B- 1049242 24-10-8 JP-C- 1568399 10-07-9 JP-A- 58113123 05-07-8 SU-A- 1514239 07-10-8 US-A- 4758598 19-07-8 EP-A-0084705 03-08-83 AU-B- 554431 21-08-8 AU-A- 9086982 16-06-8 CA-A- 1195250 15-10-8 GB-A,B 2114440 24-08-8 JP-A- 58113124 05-07-8	Patent document cited in search report	Publication date	Patent family member(s)	Publicati date
US-A- 4758598 19-0 US-A- 4758598 19-0 EP-A-0084705 03-08-83 AU-B- 554431 21-0 AU-A- 9086982 16-0 CA-A- 1195250 15-1	US-A- 4758598 19-07-8 US-A- 4758598 19-07-8 US-A- 4758598 19-07-8 EP-A-0084705 03-08-83 AU-B- 554431 21-08-8 AU-A- 9086982 16-06-8 CA-A- 1195250 15-10-8 GB-A,B 2114440 24-08-8 JP-A- 58113124 05-07-8			GB-A,B 2119246 JP-B- 1049242 JP-C- 1568399 JP-A- 58113123	25-02-86 16-11-83 24-10-89 10-07-90 05-07-83 07-10-89
QD A,D	0 7 7 07 07 07 07 07 07 07 07 07 07 07 0	 EP-A-0084705	03-08-83	US-A- 4758598 AU-B- 554431 AU-A- 9086982 CA-A- 1195250 GB-A,B 2114440	21-08-86 16-06-83 15-10-85 24-08-83
JP-A- 58113124 05-0				JP-A- 58113124	05-07-83 05-07-88
			٠		

For more details about this annex: see Official Journal of the European Patent Office, No. 12/82